Technical Data Sheet

Profile Collection Toilet Tissue Dispenser, Twin Roll – Surface Mounted

Toilet Tissue Dispensers

Profile

MasterFormat Section 10 28 13



Scan for Information





MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

6" [152] 6-1/4" [159] -3-3/4" [95] 3/4" [19] ROUNDED EDGES FLUSH RIMLESS LOCK 7" [178] MOUNTING [305] HOLES CONCEALED ON REAR WALL [302] -s RADIUS HINGE PIVOT **EDGE** [70] [41]

NOTE:

ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

PRODUCT OVERVIEW

Type 304 stainless steel cabinet with mechanism for theft-resistant spindles holds 2 rolls up to 5-1/4" diameter [Ø133] (1800 sheets); the top roll automatically drops in place when the bottom roll is used up.

KEY FEATURES & SPECIFICATIONS

- Robust 18 gauge Stainless Steel face
- Curved (radius) edges add elegance
- 22 gauge Type 304 Stainless Steel Satin Finish
- Surface Mounted
- 3/16" [5] CONCEALED piano hinge adds durability
- Double Roll Paper Towel Dispenser up to 800 ft. Length
- Held closed with a flush rimless tumbler lock

Model: #9030 Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023

| O PERATION | & | MAIN | TENANCE |
|-------------------|---|------|---------|
|-------------------|---|------|---------|

Reloading instructions are printed on graphic label inside door. Bottom roll is depleted prior to top roll automatically dropping into lower position for use. Empty rollers cannot be removed without key unlocking door.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

| Property | Value |
|--------------|---|
| Dimensions | 6" [152] W x 12" [305] H x 6-1/4" [159] D |
| Construction | Type 304 Stainless Steel - Satin Finish 3/16" CONCEALED piano hinge adds durability |
| Mounting | Surface Mounted |
| Capacity | Double Roll PaperTowel Dispenser - up to 800 ft. Length |

INSTALLATION

Unit is surface mounted on wall or partition using four (4) 1/4" x 1" [M6 x 25] Philips pan-head self-threading screws (by others) through slots on rear wall into suitable wall preparation (by others). Top two (2) mounting holes through back are "keyhole" slots for ease in hanging unit on pre-installed screws. Bottom two (2) mounting holes are horizontal slots for ease of adjustment. For compliance with 2010 ADA Accessibility Standards and 2015 ABA Standards install unit so that center line of dispenser is 7" [178] min to 9" max [229] and axis of bottom roll is 15" [381] min to 48" [1219] max AFF (Above Finished Floor).

OPTIONS

WARRANTY

One (1) Year from date of Invoice

Model: #9030 Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023