

Product Specification Sheet

**Prozone®**



<b>VECTAIR MODEL</b>	PROZONE®
<b>DESCRIPTION</b>	OZONE GENERATOR
<b>PRODUCT CATEGORY</b>	AIR CARE
<b>PRODUCT CODE / BARCODE</b>	<p><b>PROZ-WNP</b> (Non-Programmable) X1 = 5060060070271 X6 = 5060060070288</p> <p><b>PROZ-WP</b> (Programmable) X1 = 5060060070202 X6 = 5060060070264</p>

<b>Product Description</b>	<b>Prozone®</b> a safe ozone generator that kills up to 99.5% of airborne bacteria, eliminates bad odours and smells. Approved by TÜV SÜD to the standard BS/EN60335 parts 1 and 2 - the first ever ozone generator to achieve this standard.			
<b>Feature(s) and Benefit(s)</b>	<ul style="list-style-type: none"> <li>■ Non-programmable versions available - for 24/7 use in transient areas such as washrooms.</li> <li>■ Programmable version with in-built programmable timer – operates when you need it to suit location conditions.</li> <li>■ Suitable for either portable or fixed installation, for use in areas such as hotels, nursing homes, hospitals etc.</li> <li>■ Offers excellent cost in use, consuming only 14 watts of electricity.</li> <li>■ Produces ozone at safe levels, penetrating to even the most inaccessible locations.</li> <li>■ Variable output gives flexibility to suit different room sizes.</li> <li>■ Compact and Discreet.</li> <li>■ No cost private label feature.</li> <li>■ Optional colour grilles.</li> <li>■ Easier to service. Servicing can generally be accomplished in less than 5 minutes.</li> <li>■ Effective odour neutraliser.</li> <li>■ Tough fire retardant ABS plastic case.</li> <li>■ High frequency electronic power circuitry for reliability and optimum performance</li> <li>■ Automatic power cut-off to ensure safe servicing</li> <li>■ Self-locking lid with security key lock.</li> <li>■ Incorporates patent protected ceramic chip corona discharge technology.</li> </ul>			
<b>Ozone Output (mg/hr) +/- 20%</b>	Variable 2 - 80			
<b>Critical Product Dims (H x W x D )</b>	<b>mm</b>	210 x 135 x 85	<b>inches</b>	8.27 x 5.31 x 3.35
<b>Net Weight</b>	<b>kg</b>	0.980	<b>lb</b>	2.16
<b>Gross weight</b>	<b>kg</b>	1.250	<b>lb</b>	2.76
<b>x 6 Carton Dimensions ( H x W x D )</b>	<b>mm</b>	386 x 396 x 316	<b>inches</b>	15.2 x 15.59 x 12.44

<b>Colour Option(s)</b>	White Cover – Choice of White or Chrome inserts
<b>Material(s)</b>	Fire retardant ABS
<b>Warranty</b>	2 Year
<b>Packing Specification(s)</b>	1 or 6 x Individual cartons packed in an outer carton
<b>Minimum Order Quantity</b>	1
<b>Palette Quantity</b>	27 cases (162 units)
<b>Approval(s)</b>	<ul style="list-style-type: none"> <li>■ CE, TÜV SÜD (Certificate No. Z1 13 06 85104 001)</li> <li>Tested according to: EN 60335-2-65/A15:2011</li> <li>EN 60335-1/A15:2011</li> <li>EN 62233:2008</li> </ul>
<b>Operating Conditions</b>	<ul style="list-style-type: none"> <li>■ Mains input: 100-240V</li> <li>■ Rated Frequency: 50-60Hz</li> <li>■ Rated Power: 14W</li> <li>■ Protection Class: Class II</li> <li>■ Fuse rating = 5A</li> <li>■ Mains Plug: EU Plug c/w Schuko Converter Plug to BS1363-5 13A Class II</li> <li>■ Ingress Protection: IPX0</li> <li>■ Ambient temperature: 10–35°C operating; -10–60°C non-operating</li> <li>■ Humidity: 20-80% non-condensing.</li> </ul>
<b>Notes.</b>	Ozone output measured at a relative humidity of 35% at 22°C. Different environmental conditions will affect the ozone output of the generator.

Note: Features, specifications are subject to change without notification.